




Egenskaper



- Speciellt designat för att installeras i alla typer av karuselldörrar. Två möjliga layouter finns med skräddarsydda dimensioner.
- Självständig konstruktion gjord av galvaniserad stål, målad med strukturell vit epoxy-polyesterfärg RAL9016 som standardAndra färger eller rostfritt stål är tillgänglig vid efterfrågan
- Stor fasetterad insugskydd som undviker höga underhållskrav
- Cirkulär anodiserad
- centrifugalfäktar med dubbla intag drivna av en extern roteringsmotor med låg ljudvolym med 5 valbara hastigheter.EC modeller konstruerade med högeffektivitetsfläktar
- "P"-typ med vattenuppvärmda spolar"E"-typ med elektroniskt skyddade element, tresteg med integrerad reglering."A"-typ utan uppvärmning, endast luft.Valbar DX-expansionsspole
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 10m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
 - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
 - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.

Specifikationer

50Hz

ouppvärmd				
Modell	(m³/h)		(m)	
ROTO BB 1000 A	5-7			
ROTO BB 1500 A	5-7			
ROTO BB 2000 A	5-7			
ROTO BB 2500 A	5-7			
ROTO SB 1000 A	3,5-5			
ROTO SB 1500 A	3,5-5			
ROTO SB 2000 A	3,5-5			
ROTO SB 2500 A	3,5-5			

elvärmd				
Modell	(m³/h)	(kW)	(m)	(kW)
ROTO BB 1000 E	-			
ROTO BB 1500 E	-			
ROTO BB 2000 E	-			
ROTO BB 2500 E	-			
ROTO SB 1000 E	12,44			
ROTO SB 1500 E	-			
ROTO SB 2000 E	-			
ROTO SB 2500 E	-			

Vattenvärmd				
Modell	(m³/h)	(m)	(kW)	(kW)
ROTO BB 1000 P86	-			



Vattenvärmd					
Modell	(m³/h)	(m)	(kW)	(kW)	(kW)
ROTO BB 1500 P86	-				
ROTO BB 2000 P86	-				
ROTO BB 2500 P86	-				
ROTO SB 1000 P86	-				
ROTO SB 1500 P86	-				
ROTO SB 2000 P86	-				
ROTO SB 2500 P86	-				
ROTO BB 1000 P64	-				
ROTO BB 1500 P64	-				
ROTO BB 2000 P64	-				
ROTO BB 2500 P64	-				
ROTO SB 1000 P64	-				
ROTO SB 1500 P64	-				
ROTO SB 2000 P64	-				
ROTO SB 2500 P64	-				
ROTO BB 1000 P54	36,57				
ROTO BB 1500 P54	15,16				
ROTO BB 2000 P54	38,96				
ROTO BB 2500 P54	24,15				
ROTO SB 1000 P54	14,47				
ROTO SB 1500 P54	21,19				
ROTO SB 2000 P54	30,77				
ROTO SB 2500 P54	36,94				

60Hz

ouppvärmd		
Modell	(m³/h)	(m)
ROTO BB 1000 A	5-7	
ROTO BB 1500 A	5-7	
ROTO BB 2000 A	5-7	
ROTO BB 2500 A	5-7	

elvärmd				
Modell	(m³/h)	(kW)	(m)	(kW)
ROTO BB 1000 E	-			
ROTO BB 1500 E	-			
ROTO BB 2000 E	-			
ROTO BB 2500 E	-			

Vattenvärmd					
Modell	(m³/h)	(m)	(kW)	(kW)	(kW)
ROTO BB 1000 P86	-				
ROTO BB 1500 P86	-				
ROTO BB 2000 P86	-				
ROTO BB 2500 P86	-				
ROTO BB 1000 P64	-				



Modell	Vattenvärmd				
	(m³/h)	(m)	(kW)	(kW)	(kW)
ROTO BB 1500 P64	-				
ROTO BB 2000 P64	-				
ROTO BB 2500 P64	-				
ROTO BB 1000 P54	36.57				
ROTO BB 1500 P54	15.16				
ROTO BB 2000 P54	38.96				
ROTO BB 2500 P54	24.15				

Dimensioner

