Egenskaper

- Innovative concept of decorative air curtain based on a recessed model to be installed free-hanging.
- Slät frontpanel som kan anpassas med logotyper, ljus, skrift eller säkerhetssignaler och information i enlighet med beställarens instruktioner.
- Self-supporting casing construction made of galvanized steel plate painted in grey RAL9006. Andra färger tillgängliga vid efterfrågan
- Inlet and Outlet inbuilt in the same grid painted in white RAL9016. Andra färger tillgängliga vid efterfrågan
- Anodiserad uttag i aluminium, luftfolieformade.
- Tysta vridna korsflödesfläktar drivna av en extern rotormotor med två hastigheter.
- "P" type with water heated coil and integrated regulation for ON/OFF or three stages 0-10V proportional valve. "E"-typ med elektroniskt skyddade element, tresteg med integrerad reglering."A"-typ utan uppvärmning, endast luft.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
  • Auxiliary temperature sensors that improve air curtain control and increase energy savings.
  • Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.

Specifikationer

50Hz

ouppvärmd		
Modell	(m³/h)	(m)
TOP 1000 A	3.5	
TOP 1500 A	3.5	
TOP 2000 A	3.5	

elvärmd			
Modell	(m³/h)	(kW)	(m)
TOP 1000 E	3.5		
TOP 1500 E	3.5		
TOP 2000 E	3.5		

Vattenvärmd			
Modell	(m³/h)	(kW)	(m)
TOP 1000 P86	3.5		
TOP 1500 P86	3.5		
TOP 2000 P86	3.5		
TOP 1000 P64	3.5		
TOP 1500 P64	3.5		
TOP 2000 P64	3.5		

Dimensioner